

## CORRUGATED SIDEWALL ROLL-IN REFRIGERATOR RACKS 208 SERIES (FOR 18" X 26" PANS)

### FEATURES AND BENEFITS:

- Durable rack specifically designed to fit roll-in or pass through refrigerators, freezers, and warming cabinets; eliminates unnecessary product handling while maintaining proper temperature levels. Holds 18" x 26" pans.
- Fully welded framework of structural aluminum extrusions for rigidity and durability.
- Constructed of non-corrosive, Hi-Tensil aluminum for strength.
- Corrugated sidewalls securely hold 18" x 26" pans on 1-1/2" centers without tipping. Provides added strength.
- Inboard heavy duty 5" swivel casters, two with brakes. Wheel placement permits easy "in-and-out" of roll-ins.
- Two styles available; Custom (C) or Deluxe (D). Deluxe includes perimeter bumper and enclosed base.



208-1835C




### ACCESSORIES and OPTIONS (Available at extra cost):





- Pan Stop
- Corner Bumpers
- Vertical Bumpers
- Various Caster Options

See page G-36 for accessory details.

## 208 Roll-In Series (18" x 26" pans)



DETAIL OF  
PAN SLIDE



INBOARD CASTER PLACEMENT

### CUSTOM ("C")

CRES COR MODEL NO.	PAN			DIM "A"	DIM "B"	DIM "C"	INSIDE DIMENSIONS				WEIGHT ACT.
	CAP	SIZE		WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH	HEIGHT		
208-1835-C	35	18 x 26	IN	20-11/16	25-1/8	64-1/2	18-1/8	24-3/8	55-15/16	LBS	65
		460 x 660	MM	525	640	1640	460	620	1425	KG	29

### DELUXE ("D")

CRES COR MODEL NO.	PAN			DIM "A"	DIM "B"	DIM "C"	INSIDE DIMENSIONS				WEIGHT ACT.
	CAP	SIZE		WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH	HEIGHT		
208-1835-D	35	18 x 26	IN	22-9/16	27	64-1/2	18-1/8	24-3/8	55-15/16	LBS	70
		460 x 660	MM	575	690	1640	460	620	1425	KG	32

Note: Send sample pan or tray with order when using any that are not 18" x 26" pans with heavy beaded edges.

ALL ALUMINUM CONSTRUCTION IS RIVETED, WELDED AND FINISHED.

#### RACK:

- Posts: Extruded channels, 1-1/16 x 2 x .125.
- Top and bottom: Extruded channels, 1-1/16 x 2-3/8 x .188; welded to posts.
- Tie rods (2): 5/16 dia. steel rods enclosed in aluminum tubing; fastened to posts.
- Sides: .063 aluminum corrugations riveted to posts.
- Bolsters: Formed .190 aluminum; welded to posts, casters attached.
- Casters: 5" dia., swivel, modulus tires, 1-1/4 wide, load cap. 250 lbs. each, temp. range -45°/+180°F. Delrin bearings. Two casters equipped with brakes.

#### DELUXE ("D") MODELS:

- Base plate: One piece .063 aluminum.
- Bumper: 1" wide gray rubber, perimeter type.

#### PAN SLIDES:

- Corrugations act as pan slides on 1-1/2" centers.

#### SHORT FORM SPECIFICATIONS

Cres Cor Roll-In Refrigerator Rack Model 208-1835- (C) or (D). Extruded aluminum welded construction. Tie rods (2) applied at front and rear. No-tip corrugated sides for (35) 18" x 26" pans on 1-1/2" centers. Inboard 5" swivel modulus casters, Delrin bearings. Load capacity 250 lbs. each, temperature -45° to +180°F.

Custom Model (C)

Deluxe Model (D) has .063 aluminum base plate; perimeter bumper.

2 year parts warranty. Provide the following accessories:  
\_\_\_\_\_. NSF listed.



5925 Heisley Road • Mentor, OH 44060-1833  
Phone: 877/CRESCOR • Fax: 440/350-7267  
www.crescor.com

© Crescent Metal Products, Inc. 2006 All rights reserved.

*In line with its policy to continually improve its products, CRES COR reserves the right to change materials and specifications without notice.*

Litho in U.S.A.