

QUEEN MARY RACKS 271 SERIES


FEATURES AND BENEFITS:

- Durable Queen Mary rack ideal for transporting plated banquet meals and returning soiled dishware to ware washing area.
- All riveted framework of structural aluminum extrusions for rigidity and durability.
- Constructed of non-corrosive, Hi-Tensile aluminum for strength.
- Shelves have raised “marine” edges; prevents tray slide and retains spillage.
- Two models available:
 - 5 shelves on 11" centers - Model 271-51-5927
 - 6 shelves on 8" centers - Model 271-61-5927
- Side mounted push handles for ease of transporting.
- Standard perimeter bumper protects surfaces.
- Heavy duty 8" polyurethane casters, two swivel with brakes, make maneuvering easy.



ACCESSORIES and OPTIONS (Available at extra cost):

- Stainless Steel Shelves



CRES-COR MODEL NO.	NO. OF SHELVES		DIM "A"	DIM "B"	DIM "C"	INSIDE DIMENSIONS			WEIGHT ACT.	
			WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH	*HEIGHT		
271-51-5927	5	IN	62-1/4	29	62-11/16	55-1/4	25	11	LBS	156
		CM	158.1	73.7	159.2	140.3	63.5	27.9	KG	71
271-61-5927	6	IN	62-1/4	29	62-11/16	55-1/4	25	8	LBS	156
		CM	158.1	73.7	159.2	140.3	63.5	20.3	KG	71

NOTES: 1. For oval tray sizes: 20-3/4" x 25-1/2", 22-3/4" x 27-5/8" and 23-1/2" x 29". Two trays per shelf.
 2. *Inside height dimension is between shelves.

ALL ALUMINUM CONSTRUCTION IS RIVETED, WELDED AND FINISHED.

RACK:

- Posts: Extruded channels, 1 x 2 x .125.
- Shelves: Formed one piece .063 aluminum with marine edges; reinforced with .063 aluminum channels.
 Optional stainless steel shelves are 16 ga. type 304.
 271-51-5927: Five shelves spaced on 11" centers.
 271-61-5927: Six shelves spaced on 8" centers.
- Shelf corners and bottom gussets: .100 aluminum riveted to posts and shelves.
- Push handles (2): 1" dia. aluminum tubing, gray plastic coated.
- Bolsters: Formed .190 aluminum; welded to posts, casters attached.
- Casters: 8" dia., polyurethane tires, 1-1/4 wide, load cap. 400 lbs. each, temp. range -30°/+180°F. Bearings are sealed and permanently lubricated. Two swivel casters equipped with brakes and two rigid casters.
- Bumper: 1" wide gray rubber, perimeter type.

SHORT FORM SPECIFICATIONS

Cres-Cor Queen Mary Rack Model 271-___-5927. Extruded aluminum construction reinforced with riveted gussets. (___) aluminum (or) stainless steel shelves with marine edges on (___) centers. Push handle on each end. 8" polyurethane casters, 2 swivel, 2 rigid, permanently lubricated, sealed ball bearings. Load capacity 400 lbs. each, temperature -30° to +180°F. 2 year parts warranty. NSF listed.

