

CORRUGATED SIDEWALL HALF-SIZE UTILITY RACK MODEL 280-1818

FEATURES AND BENEFITS:

- Durable half-size utility rack ideal for extra work table or mobile appliance center.
- Reinforced stainless steel top provides a sanitary surface.
- Fully welded framework of structural aluminum extrusions for rigidity and durability.
- Constructed of non-corrosive, Hi-Tensile aluminum for strength.
- Corrugated sidewalls securely hold 18" x 26" pans on 1-1/2" centers without tipping. Provides added strength.
- Offers complete flexibility for operator's selection of pan spacing. Eliminates potential of product damage.
- Heavy duty 5" swivel casters, two with brakes. Provides mobility when fully loaded.



280-1818



ACCESSORIES and OPTIONS (Available at extra cost):

- Cutting Board and Pan Assembly
- Pan Stop
- Corner Bumpers
- Vertical Bumpers
- Perimeter Bumper
- Rotary Bumpers (for use with 5" casters)
- Floor Lock (for use with 5" casters)
- Various Caster Options

See page G-36 for accessory details.

CRES-COR MODEL NO.	PAN			DIM "A"	DIM "B"	DIM "C"	INSIDE DIMENSIONS			WEIGHT ACT.	
	CAP	SIZE		WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH	HEIGHT		
280-1818	18	18 x 26	IN	21-13/16	26-15/16	36-1/16	18-1/16	26	27-13/16	LBS	62
		45.7 x 66.0	CM	55.4	68.4	91.6	45.9	66.0	70.6	KG	28

NOTES: 1. Send sample pan or tray with order when using any that are not 18" x 26" with heavy beaded edges.
 2. When ordering bumpers, add 2" to overall dimensions.

ALL CONSTRUCTION IS RIVETED, WELDED AND FINISHED.

RACK:

- Top: Formed 16 ga. 304 stainless steel.
- Top, bottom and reinforcement channels: Extruded aluminum, 1-1/16 x 2-3/8 x .188; welded to posts.
- Posts: Aluminum closed post extrusions, 1-1/16 x 2.
- Sides: .063 aluminum corrugations riveted to posts.
- Casters: 5" dia., swivel, neoprene tires, 1-1/4 wide, load cap. 200 lbs. each, temp. range -20°/+160°F. Bearings are sealed and permanently lubricated. Two casters equipped with brakes.

PAN SLIDES:

- Corrugations act as pan slides on 1-1/2" centers.

SHORT FORM SPECIFICATIONS

Cres-Cor Half-Size Utility Rack Model 280-1818. Extruded aluminum welded construction with 16 ga. 304 stainless steel top. No-tip corrugated sides for (18) 18" x 26" pans on 1-1/2" centers. 5" swivel neoprene casters, permanently lubricated, sealed ball bearings. Load capacity 200 lbs. each, temperature -20° to +160°F. 2 year parts warranty. Provide the following accessories: _____. NSF listed.



5925 Heisley Road • Mentor, OH 44060-1833
 Phone: 877/CRESCOR • Fax: 440/350-7267
 www.crescor.com

© Crescent Metal Products, Inc. 1998 All rights reserved.

In line with its policy to continually improve its products, CRES-COR reserves the right to change materials and specifications without notice.

Litho in U.S.A.