

CHANNEL SLIDE DOUBLE TRAY RACK MODEL 2213-1824B

FEATURES AND BENEFITS:

- Versatile double tray rack for transporting meal trays and bussing afterwards. Rack holds 14" x 18" trapezoid trays as well as 13" x 18", 14" x 18", and 18" x 26" standard pans.
- Rack can be enclosed on sides and back for use as an attractive tray return cart.
- Fully welded framework of structural aluminum extrusions for rigidity and durability.
- Constructed of non-corrosive, Hi-Tensile aluminum for strength.
- Special "sure-hold" extrusions, riveted in place on 5-1/8" centers, securely hold tray's top and bottom; will not tip even when pulled half way out.
- Heavy duty 5" swivel casters, two with brakes. Provides mobility when fully loaded.



ACCESSORIES and OPTIONS (Available at extra cost):

- Top Enclosure
- Side Enclosure
- Back Enclosure
- Bottom Enclosure
- Pan Stops
- Push Handle
- Corner Bumpers
- Vertical Bumpers
- Perimeter Bumper
- Rotary Bumpers (for use with 5" casters)
- Floor Lock (for use with 5" casters)
- Various Caster Options

See page G-36 for accessory details.

CRES-COR MODEL NO.	PAN			DIM "A"	DIM "B"	DIM "C"	INSIDE DIMENSIONS				WEIGHT ACT.
	CAP	SIZE		WIDTH	DEPTH	HEIGHT	*WIDTH	DEPTH	HEIGHT		
2213-1824B	48	13 x 18	IN	42-3/16	30-1/4	69-9/16	18-3/4	29-1/2	61-3/8	LBS	122
		33.0 x 45.7	CM	107.2	76.8	176.7	47.6	74.9	155.9	KG	53
	48	14 x 18	IN								
		35.6 x 45.7	CM								
	24	18 x 26	IN								
		45.7 x 66.0	CM								
	48	Trapezoid 14 x 18	IN								
		35.6 x 45.7	CM								

*Inside width dimension for each compartment.
When ordering bumpers, add 2" to overall dimensions.

ALL ALUMINUM CONSTRUCTION IS RIVETED, WELDED AND FINISHED.

RACK:

- Posts: Closed post extrusions, 1-1/16 x 2.
- Top and bottom: Extruded channels, 1-1/16 x 2-3/8 x .188; welded to posts.
- Casters: 5" dia., swivel, neoprene tires, 1-1/4 wide, load cap. 200 lbs. each, temp. range -20°/+160° F. Bearings are sealed and permanently lubricated. Two casters equipped with brakes.

PAN SLIDES:

- Extruded channels, 15/16 x 1-7/16 x 2-1/2 x .100; riveted to posts on 5-1/8" centers.

SHORT FORM SPECIFICATIONS

Cres-Cor Double Tray Rack Model 2213-1824B. Extruded aluminum welded construction with no-tip "C" type channel slides riveted on 5-1/8" centers. Capacity (48) 14" x 18" trapezoid or (24) 18" x 26" pans. 5" swivel neoprene casters, permanently lubricated, sealed ball bearings. Load capacity 200 lbs. each, temperature -20° to +160° F. 2 year parts warranty. Provide the following accessories: _____. NSF listed.



5925 Heisley Road • Mentor, OH 44060-1833
Phone: 877/CRESCOR • Fax: 440/350-7267
www.crescor.com

© Crescent Metal Products, Inc. 1998 All rights reserved.

In line with its policy to continually improve its products, CRES-COR reserves the right to change materials and specifications without notice.

Litho in U.S.A.